

CADRE

C:62® Monocoque Advanced Twin Mold Technology, Aluminium 6061 T6 Rear Triangle, Efficient Trail Control, FSP 4-Link, Agile Trail Geometry, Boost 148, UDH™, Fully Integrated Battery, Advanced Internal Cable Routing

TAILLE

Size Split: 27.5: S (16") // 29: M (18"), L (20"), XL (22")

FOURCHE SUSPENDUE

Fox 36 Float Performance GRIP, 3-Position w/Micro Adjust, Tapered, 15x110mm, E-Bike Optimized, 150mm

AMORTISSEUR

Fox Float X Performance, 205x60mm (27.5: 185x55mm), Trunion Mount, Adjustable LSR w/ 2-Pos. Lever

ENTRETOISES D'AMORTISSEUR

Top: 54mm Trunion Mount, Bottom: 22.2x8mm

MOTEUR

Bosch Drive Unit Performance CX Generation 4 (85Nm) Cruise (250Watt), Smart System



BATTERIE

Bosch PowerTube 750



TÉLÉCOMMANDE

Bosch LED Remote



ÉCRAN

Bosch Kiox 300



CHARGEUR

Bosch 4A

**FREIN**

Magura MT7, Hydr. Disc Brake (203/203)

DÉRAILLEUR ARRIÈRE

Sram GX Eagle™, 12-Speed

LEVIERS

Sram GX Eagle™ Trigger, Single Click

PLATEAU

ACID E-Crank, 165mm (27.5: 36T // 29: 34T)

GUIDE DE CHAÎNE

Reverse Flip-Guide E-Chain Guide, Direct Mount, GEN4

CASSETTE

Sram XG-1275 Eagle™, 10-52T

CHAÎNE

Sram NX Eagle™

CINTRE

Newmen Evolution SL 318.25, 800mm

POTENCE

CUBE Performance Stem E-MTB, 31.8mm

POIGNÉES

ACID Disrupt, Soft Compound

JEU DE DIRECTION

ACROS AZF-1035, ICR (Integrated Cable Routing), BlockLock 120°, Top Zero-Stack 1 1/2" (ZS 56mm), Bottom Zero-Stack 1 1/2" (ZS 56mm)

ROUES

Newmen Performance 30, 28/28 Spokes, 15x110mm/12x148mm, Tubeless Ready

PNEU AVANT

Maxxis Assegai, MaxxGrip/EXO+, Tubeless Ready, 2.5 WT

PNEU ARRIÈRE

Maxxis Minion DHR II, MaxxGrip/DoubleDown, Tubeless Ready, 2.4 WT

TIGE DE SELLE

CUBE Dropper Post, Handlebar Lever, Internal Cable Routing, 31.6mm

SELLE

Natural Fit Venec

POIDS

24,6 kg