

CADRE

C:62® Monocoque Advanced Twin Mold Technology, Aluminium 6061 T6 Rear Triangle, Efficient Trail Control, FSP 4-Link, Agile Trail Geometry, Boost 148, UDH™, Fully Integrated Battery, Advanced Internal Cable Routing

TAILLE

Size Split: 27.5: S (16") // 29: M (18"), L (20"), XL (22")

FOURCHE SUSPENDUE

Fox 36 Float Factory FIT4, 3-Position w/Low Speed Compression Adjust, Tapered, 15x110mm, E-Bike Optimized, 150mm, Kashima Coated

AMORTISSEUR

Fox Float X Factory, 205x60mm (27.5: 185x55mm), Adjustable LSC w/ 2-Pos. Lever, Trunnion Mount, Kashima Coated

ENTRETOISES D'AMORTISSEUR

Top: 54mm Trunnion Mount, Bottom: 22.2x8mm

MOTEUR

Bosch Drive Unit Performance CX Generation 4 (85Nm) Cruise (250Watt), Smart System



BATTERIE Bosch PowerTube 750



TÉLÉCOMMANDE Bosch LED Remote



ÉCRAN Bosch Kiox 300



CHARGEUR Bosch 4A



FREIN

Shimano XT BR-M8120, Hydr. Disc Brake (203/203)

DÉRAILLEUR ARRIÈRE

Shimano XT RD-M8100-SGS, ShadowPlus, 12-Speed

LEVIERS

Shimano XT SL-M8100-IR, Direct Attach

PLATEAU

e*thirteen Plus Crank, 165mm (27.5: 36T // 29: 34T)

GUIDE DE CHAÎNE

Reverse Flip-Guide E-Chain Guide, Direct Mount, GEN4

CASSETTE

Shimano XT CS-M8100, 10-51T

CHAÎNE

Shimano XT CN-M8100

CINTRE

Newmen Advanced 318.25, Carbon, 780mm

POTENCE

CUBE Performance Stem E-MTB, 31.8mm

POIGNÉES

ACID Disrupt, Soft Compound

JEU DE DIRECTION

ACROS AZF-1035, ICR (Integrated Cable Routing), BlockLock 120°, Top Zero-Stack 1 1/2" (ZS 56mm), Bottom Zero-Stack 1 1/2" (ZS 56mm)

ROUES

Newmen Evolution SL E.G. 30, 28/28 Spokes, 15x110mm/12x148mm, Tubeless Ready

PNEU AVANT

Schwalbe Magic Mary, Super Trail, Addix Soft, Kevlar, 2.4

PNEU ARRIÈRE

Schwalbe Big Betty, Super Gravity, Addix Soft, Kevlar, 2.4

TIGE DE SELLE

Fox Transfer Factory 31.6mm, Kashima Coated

SELLE

Natural Fit Venec

POIDS

24,2 kg

-