

CADRE

C:62® Monocoque Advanced Twin Mold Technology, Aluminium 6061 T6 Rear Triangle, Efficient Trail Control, FSP 4-Link, Agile Trail Geometry, Boost 148, UDH™, Fully Integrated Battery, Advanced Internal Cable Routing

TAILLE

Size Split: 27.5: S (16") // 29: M (18"), L (20"), XL (22")

FOURCHE SUSPENDUE

Fox 34 Float Rhythm, 2-Position Sweep-Adjust GRIP Damper, Tapered, 15x110mm, E-Bike Tune, 150mm

AMORTISSEUR

Fox Float DPS EVOL, 205x60mm (27.5: 185x55mm), Open/Medium/Firm Mode, Trunnion Mount

ENTRETOISES D'AMORTISSEUR

Top: 54mm Trunnion Mount, Bottom: 22.2x8mm

MOTEUR

Bosch Drive Unit Performance CX Generation 4 (85Nm) Cruise (250Watt), Smart System



BATTERIE Bosch PowerTube 750



TÉLÉCOMMANDE Bosch LED Remote



ÉCRAN Bosch Kiox 300



CHARGEUR Bosch 4A

**FREIN**

Shimano XT BR-M8120, Hydr. Disc Brake (203/203)

DÉRAILLEUR ARRIÈRE

Shimano XT RD-M8100-SGS, ShadowPlus, 12-Speed

LEVIERS

Shimano Deore SL-M6100-IR, Direct Attach, Rapidfire-Plus

PLATEAU

ACID E-Crank, 165mm (27.5: 36T // 29: 34T)

GUIDE DE CHAÎNE

Reverse Flip-Guide E-Chain Guide, Direct Mount, GEN4

CASSETTE

Shimano Deore CS-M6100, 10-51T

CHAÎNE

Shimano CN-M6100

CINTRE

Newmen Evolution SL 318.25, 780mm

POTENCE

CUBE Performance Stem E-MTB, 31.8mm

POIGNÉES

ACID Disrupt, Soft Compound

JEU DE DIRECTION

ACROS AZF-1035, ICR (Integrated Cable Routing), BlockLock 120°, Top Zero-Stack 1 1/2" (ZS 56mm), Bottom Zero-Stack 1 1/2" (ZS 56mm)

ROUES

Newmen Performance 30, 28/28 Spokes, 15x110mm/12x148mm, Tubeless Ready

PNEU AVANT

Schwalbe Hans Dampf, Addix Soft, Super Trail, Tubeless Easy, 2.6

PNEU ARRIÈRE

Schwalbe Hans Dampf, Addix Speedgrip, Super Trail, Tubeless Easy, 2.6

TIGE DE SELLE

CUBE Dropper Post, Handlebar Lever, Internal Cable Routing, 31.6mm

SELLE

Natural Fit Venec

POIDS

24,1 kg