

SPÉCIFICATIONS

Cadre SMOOTHWALL™ Carbon | Full Sealed Cartridge Bearings | Press Fit BB | Internal Cable Routing | 2-Bolt ISCG05 Tabs | RIDE-9™ Adjustable

Geometry | 2 Position Axle | 140mm Travel. SMOOTHWALL™ Carbon

Rear Triangle

Fourche Marzocchi Z2 Float EVOL Rail 150mm | 44mm Oset

Débattement avant 150

Amortisseur Fox Float DPS Performance | Sealed Bearing Eyelet | 25x8mm F Hardware | XS - SM = 190x45mm | MD - LG - XL = 210x52.5mm | SizeSpecic
tune

in

FAQ

Débattement arrière 140mm

Jeu de direction FSA Orbit NO.57E | Sealed 36°x45° Bearings | 30.2mm x 41mm

x

7.1mm Upper | 40mm x 51.8mm x 7.5mm Lower | 1.5" Crown Race

Potence Rocky Mountain 31.8 AM | 5° Rise | All Sizes = 40m

Cintre Rocky Mountain AM | 780mm Width | 25mm Rise | 9° Backsweep | 5°

Upsweep | 31.8 Clamp

Poignets Rocky Mountain Lock On Light

Freins Shimano MT4120 4 Piston | Resin Pads | F:Shimano RT30 180mm |

R:Shimano RT30 180mm

Commandes de vitesses

Shimano Deore 12spd

Derailleur arrière Shimano Deore 12spd

Pédalier et plateau Shimano Deore | 32T | 24mm Spindle | 170mm Crank

Length

Boitier de pédalier Shimano SM-BBMT500

Cassette Shimano Deore 10-51T 12spd

Chaîne Shimano M6100

Moyeux avant Rocky Mountain Sealed Boost 15mm

Moyeux arrière Novatec D462 Sealed Boost 148mm

Rayons 2.0 Stainless

Jantes WTB ST i30 TCS 2.0 Tubeless | 32H | Tubeless Ready - Tape / Valves

Incl

Pneus F: Maxxis Minion DHF 2.5 WT EXO Tubeless Ready // R: Maxxis Minion

DHR II 2.4 WT EXO Tubeless Ready

Tige de selle Rocky Mountain Toonie Drop Composite 30.9mm | XS - SM =
125mm |

MD = 150mm | LG - XL = 170mm

Selle WTB Volt Race 142

Poids N.C