

SPÉCIFICATIONS

Cadre SMOOTHWALL™ Carbon | Full Sealed Cartridge Bearings | Press Fit BB | Internal Cable Routing | 2-Bolt ISCG05 Tabs | RIDE-9™ Adjustable

Geometry | 2 Position Axle | 140mm Travel. SMOOTHWALL™ Carbon Rear Triangle

Fourche Fox 36 Float EVOL FIT4 Performance Elite Series 150mm | 27.5 = 37mm Oset | 29 = 44mm Oset

Débattement avant 150

Amortisseur Fox Float X Performance Elite | Sealed Bearing Eyelet | 25x8mm F Hardware | XS - SM = 190x45mm | MD - LG - XL = 210x52.5mm | Size-Specific tune in FAQ

Débattement arrière 140mm

Jeu de direction FSA Orbit NO.57E | Sealed Stainless 36°x45° Bearings | 30.2mm x

41mm x 7.1mm Upper | 40mm x 51.8mm x 7.5mm Lower | 1.5" Crown Race

Potence Rocky Mountain 35 AM | 5° Rise | All Sizes = 40mm

Cintre Rocky Mountain AM | 780mm Width | 25mm Rise | 9° Backsweep | 5° Upsweep | 35 Clamp

Poignets ODI Elite Pro Lock On

Freins Shimano XT Trail 4 Piston | Metal Pads | F:Shimano RT66 180mm | R:Shimano RT66 180mm

Commandes de vitesses

Shimano XT

Derailleur arrière Shimano XT

Pédalier et plateau Shimano XT | 32T | 24mm Spindle | Crankarm Length: XS = 165mm

Crankarm | SM - XL = 170mm

Boitier de pédalier Shimano SM-BBMT500

Cassette Shimano XT 10-51T

Chaîne Shimano M8100

Moyeux avant Rocky Mountain Sealed Boost 15mm

Moyeux arrière DT Swiss 370 Boost 148mm | 18T Star-Ratchet

Rayons DT Swiss Competition 2.0/1.8/2.0

Jantes Race Face AR 30 | 32H | Tubeless Ready - Tape / Valves Incl

Pneus F: Maxxis Minion DHF 2.5 WT 3C MaxxTerra EXO+ Tubeless Ready // R:

Maxxis Minion DHR II 2.4 WT 3C MaxxTerra EXO+ Tubeless Ready

Tige de selle Race Face Turbine R (by Fox) Dropper 30.9mm | XS - SM =
125mm |

MD = 150mm | LG = 175mm | XL = 200mm

Selle WTB Volt Race 142

Poids N.C