

SPÉCIFICATIONS

Cadre SMOOTHWALL™ Carbon | Full Sealed Cartridge Bearings | Press Fit BB | Internal Cable Routing | 2-Bolt ISCG05 Tabs | RIDE-9™ Adjustable

Geometry | 2 Position Axle | 160mm Travel. SMOOTHWALL™ Carbon

Rear Triangle

Fourche Fox 38 Float EVOL GRIP2 Factory Series 170mm | 27.5 = 37mm Oset | 29 = 44mm Oset

Débattement avant 170

Amortisseur Fox Float X2 Factory | Sealed Bearing Eyelet | 25x8mm F Hardware |

SM = 210x55mm | MD - LG - XL = 230x60mm | Size-Specific tune in

Débattement arrière 160

FAQ

Jeu de direction FSA Orbit NO.57E | Sealed Stainless 36°x45° Bearings | 30.2mm x

41mm x 7.1mm Upper | 40mm x 51.8mm x 7.5mm Lower | 1.5" Crown Race

Potence Race Face Turbine R | 0° Rise | All Sizes = 40mm

Cintre Race Face Next R | 780mm Width | 35mm Rise | 8° Backsweep | 4° Upsweep | 35mm Clamp

Poignets ODI Elite Pro Lock On

Freins Shimano XTR Trail 4 Piston | IceTec Metal Pads | F:Shimano RT86 203mm | R:Shimano RT86 203mm

Commandes de vitesses

Shimano XTR

Dérailleur arrière Shimano XTR

Pédalier et plateau Race Face Turbine Cinch | 32T | 30mm Spindle | 170mm Crank Length

Boitier de pédalier Race Face BB92 30mm

Cassette Shimano XTR 12s 10-51T

Chaîne Shimano XTR 12s

Moyeux avant DT Swiss 350 Boost 15mm

Moyeux arrière DT Swiss 350 Boost 148mm | 36T Star-Ratchet

Rayons DT Swiss Competition 2.0/1.8/2.0

Jantes Race Face ARC Carbon 31 | 32H | Tubeless Ready - Tape / Valves Incl

Pneus F: Maxxis Assegai 2.5 WT 3C MaxxGrip DD Tubeless Ready // R: Maxxis

Minion DHR II 2.4 WT 3C MaxxTerra DD Tubeless Ready

Tige de selle Fox Transfer Factory Series 30.9mm | SM = 125mm | MD =

150mm | LG

= 175mm | XL = 200mm

Selle WTB Volt Race 142

Poids This information isn't available yet. We will update the weight of this model as soon as possible.