

# RACE SPEC

## FRAME

### UNNO DASH

Carbon fibre monocoque with 140mm of rear travel.

Virtual pivot suspension system. Integrated chain guide and seat tube clamp. Down tube protector. EnduroMAX

Bearings. Internal cable routing. Boost thru axle

12x148. Post Mount brake system. Max tire width: 2.6".

**Oceanworks recycled plastic parts and rubber protectors.**

Recommended sag: 35% (+/- 5%).

## FORK

### FOX 36 FACTORY

150mm travel. Kashima coating. Grip 2 damper. 15x110 axle. Adjustments: HSC, LSC, HSR, LSR. 44mm offset.

## SHOCK

### FOX FLOAT X2 FACTORY

230x57.5mm. Kashima Coating. 2-pos lever. VVC Rebound. Adjustments: HSC, LSC, HSR, LSR.

## DERAILLEUR

### SRAM GX AXS

12-speed Eagle technology. Battery: EP Powerpack 1.

T-type

## TRIGGER

### SRAM POD AXS

Wireless. MMX. Right bridge.

## CHAIN

### SRAM GX EAGLE

120 links. T-type.

## CASSETTE

### SRAM GX

XG 1275. 10-52T. 520% range.

## CRANKSET

### SRAM GX CARBON

Carbon. DUB. 170mm. Black. 34T Chainring.

## COCKPIT

### DEUX ENDURO BARS

Integrated bars and stem. No-bolts design. Internal fork tube clamp. 800mm width, 20mm rise, 40mm stem.

## WHEELS

### DT SWISS EX 1700

29" wheels. XD mount.

## BRAKES

### FORMULA CURA 4

4X18mm pistons on caliper. SRAM Matchmaker. Sintered pads. Axial master cylinder.

## ROTORS

### FORMULA CURA ROTORS

203mm front and 180mm rear. Extreme lateral stiffness, anti-noise design and anti-vibration technology.

## FRONT TYRE

### MAXXIS ASSEGAI

29x2.50WT, 3CMaxxGrip, EXO+, TR.

## REAR TYRE

### MAXXIS MINION DHR II

29x2.50WT, 3CMaxxGrip, EXO+, TR.

## SEAT POST

### ONEUP DROPPER

Lever MMX. S1: 120 / S2: 150 / S3: 180mm travel

## SADDLE

### SELLE ITALIA SLR BOOST

Fibra-tek. Manganese.

Weight: 14.3kg (S2)