

SPÉCIFICATIONS

Cadre FORM™ Alloy | Full Sealed Cartridge Bearings | Press Fit BB | Internal Cable Routing | RIDE-4™ Adjustable Geometry | 120mm Travel. FORM™ Alloy Rear Triangle

Fourche RockShox Recon Gold 130mm | 27.5 = 37mm Oset | 29 = 42mm Oset

Débattement avant 130mm

Amortisseur RockShox Deluxe Select+ | Sealed Bearing Eyelet | 20x8mm F Hardware | All Sizes = 190x45mm | Size-Specific tune in FAQ

Débattement arrière 120mm

Jeu de direction FSA Orbit NO.57E | Sealed 36°x45° Bearings | 30.2mm x 41mm x

7.1mm Upper | 40mm x 51.8mm x 7.5mm Lower | 1.5" Crown Race

Potence Rocky Mountain 31.8 XC | 5° Rise | All Sizes = 50mm

Cintre Rocky Mountain AM | XS = 760mm | SM - XL = 780mm Width | 25mm Rise | 9° Backsweep | 5° Upsweep | 31.8 Clamp

Poignets Rocky Mountain Lock On Light

Freins Shimano MT4100 2 Piston | Resin Pads | F:Shimano RT30 180mm | R:Shimano RT30 180mm

Commandes de vitesses

Shimano Deore 12spd

Derailleur arrière Shimano Deore 12spd

Pédalier et plateau Shimano Deore | 32T | 24mm Spindle | 170mm Crank Length

Boitier de pédalier Shimano SM-BBMT500

Cassette Shimano Deore 10-51T 12spd

Chaîne Shimano M6100

Moyeux avant Shimano MT410 | 15mm Boost

Moyeux arrière Shimano MT410 Boost 148mm

Rayons 2.0 Stainless

Jantes WTB ST Light i27 TCS 2.0 Tubeless | 28H | Tubeless Ready - Tape / Valves Incl

Pneus F: Maxxis Rekon 2.4 WT EXO Tubeless Ready // R: Maxxis Rekon 2.4 WT EXO Tubeless Ready

Tige de selle Rocky Mountain Toonie Drop Composite 30.9mm | XS - SM = 125mm |

MD = 150mm | LG - XL = 170mm

Selle WTB Volt 142

Poids This information isn't available yet. We will update the weight of this model as soon as possible.