

SPÉCIFICATIONS

Cadre SMOOTHWALL™ Carbon | Integrated Display | Mid-High Pivot Smoothlink Suspension System | Press Fit BB | RIDE-4™ Adjustable Geometry + Suspension Rate | 160mm Travel. SMOOTHWALL™ Carbon Rear Triangle

Fourche Fox 38 Float EVOL GRIP2 Factory Series 170mm | 44mm Oset

Débattement avant 170mm

Amortisseur Fox DHX2 Factory | Sealed Bearing Eyelet | 25x8mm F Hardware | All

Sizes = 230x62.5mm | Size-Specific tune in FAQ

Débattement arrière 160mm

Jeu de direction FSA Orbit NO.57E | Sealed Stainless 36°x45° Bearings | 30.2mm x

41mm x 7.1mm Upper | 40mm x 51.8mm x 7.5mm Lower | 1.5" Crown Race

Potence Rocky Mountain 35 CNC | 0° Rise | All Sizes = 40mm

Cintre Race Face Turbine R | 780mm Width | 35mm Rise | 8° Backsweep | 4° Upsweep | 35mm Clamp

Poignets ODI Elite Pro Lock On

Freins Shimano XT Trail 4 Piston | Metal Pads | F:Shimano RT86 203mm | R:Shimano RT86 203mm

Commandes de vitesses

Shimano XT

Dérailleur arrière Shimano XT

Pédalier et plateau Race Face Turbine Cinch 34T | 30mm Spindle | Crank Length: SM - MD = 165mm / LG - XL = 170mm

Boitier de pédalier Race Face BB89 30mm

Cassette Shimano XT 10-51T

Chaîne Shimano M8100

Moyeux avant Rocky Mountain Sealed Boost 15mm

Moyeux arrière DT Swiss Hybrid 350 Boost 148mm | 24T Star-Ratchet

Rayons F : DT Swiss Champion 2.0 | R : DT Swiss Alpine 2.3/2.0

Jantes Race Face ARC HD 30 | 32H | Tubeless Ready - Tape / Valves Incl

Pneus F: Maxxis Assegai 2.5 WT 3C MaxxGrip DD Tubeless Ready // R: Maxxis Minion DHR II 2.4 WT 3C MaxxTerra DD Tubeless Ready

Tige de selle Fox Transfer Factory Series 30.9mm | SM = 125mm | MD = 150mm | LG

= 175mm | XL = 200mm

Selle WTB Volt Race 142

Drive System Dynamene 4.0 Mountain Bike Drive | 250w Nominal Power | 108Nm |

Rocky Mountain Micro Remote | Low RPM - High Efficiency class 1 eMTB System | Designed in Canada

Battery 720 Wh Removable Integrated Li-Ion | 100% Charged in 3:55 (4A) / 7:35 (2A) | 80% Charged in 2:55 (4A) / 6:05 (2A)

Remote Rocky Mountain Micro Remote

Display Rocky Mountain Jumbotron | Drive System Customization | Battery & Assist Level | Trip | Speed | Cadence | Top Tube Integration

Charger Rocky Mountain Powerplay FAST Charger | 4A | 48V | Higo Deep Socket Connector | Overtimepack Compatible (Dynamene 4)

Poids n.c