

# FACTORY SPEC

## FRAME

### UNNO MITH

Carbon fibre monocoque with 160mm of rear travel. Virtual pivot suspension system. Integrated display, battery, chain guide and seat tube clamp. Motor protector. EnduroMAX Bearings. Internal cable routing. Boost thru axle 12x148. Post Mount brake system. Max tire width: 2.6". **Oceanworks recycled plastic parts and rubber protectors.** Recommended sag: 35% (+/- 5%).

## MOTOR AND BATTERY

### BOSCH PERFORMANCE LINE RACE

750Wh battery. KIOX Display. Bosch Smart System.

## FORK

### FOX 38 FACTORY

170mm travel. Kashima coating. Grip 2 damper. 15X110 axle. Adjustments: HSC, LSC, HSR, LSR. 44mm offset.

## SHOCK

### FOX FLOAT X2 FACTORY

230x65mm. Kashima Coating. 2-pos lever. VVC Rebound. Adjustments: HSC, LSC, HSR, LSR.

## DERAILLEUR

### SRAM XX AXS

12-speed Eagle technology. Battery: EP Powerpack 2.

## TRIGGER

### SRAM AXS POD ULTIMATE

Right bridge. WMMX.

## CHAIN

### SRAM XX Eagle

120 links. T-type.

## CASSETTE

### SRAM XX

XG 1297. 520% range. 10-52T.

## CRANKSET

### SRAM XX

For Bosch Cap ISIS M15 SE. 165mm. With SRAM XX Chainring for Bosch Gen4 36T. T-Type.

## COCKPIT

### DEUX ENDURO BARS

Integrated bars and stem. No-bolts design. Internal fork tube clamp. 800mm width, 20mm rise, 40mm stem.

## BRAKES

### FORMULA CURA 4

4X18mm pistons on caliper. SRAM Matchmaker. Sintered pads. Axial master cylinder.

## ROTORS

### FORMULA CURA ROTORS

220mm front and 203mm rear. Extreme lateral stiffness, anti-noise design and anti-vibration technology.

## WHEELS

### DT SWISS HXC 1501

29" front and 27,5" rear. XD mount.

## FRONT TYRE

### MAXXIS ASSEGAI

29x2.50WT, 3CMaxxGrip, EXO+, TR.

## REAR TYRE

### MAXXIS MINION DHR II

27.5x2.40WT, 3CMaxxTerra, DD, TR.

## SEAT POST

### SRAM REVERB AXS

With POD trigger. Left bridge. S1: 125 / S2: 150 / S3: 175mm travel.

## SADDLE

### SELLE ITALIA SLR BOOST

Kit carbon.