

# RACE SPEC

## FRAME

UNNO MITH

Carbon fibre monocoque with 160mm of rear travel.  
Virtual pivot suspension system. Integrated display,  
battery, chain guide and seat tube clamp. Motor protector.  
EnduroMAX Bearings. Internal cable routing. Boost thru  
axle 12x148. Post Mount brake system. Max tire width:  
2.6". **Oceanworks recycled plastic parts and rubber  
protectors.** Recommended sag: 35% (+/- 5%).

## MOTOR AND BATTERY

BOSCH PERFORMANCE LINE CX GEN4

750Wh battery. KIOX Display. Bosch Smart System.

## FORK

FOX 38 FACTORY

170mm travel. Kashima coating. Grip 2 damper. 15x110  
axle. Adjustments: HSC, LSC, HSR, LSR. 44mm offset.

## SHOCK

FOX FLOAT X2 FACTORY

230x65mm. Kashima Coating. 2-pos lever. VVC Rebound.  
Adjustments: HSC, LSC, HSR, LSR.

## DERAILLEUR

SRAM GX AXS

12-speed Eagle technology. Battery: EP Powerpack 1.

## TRIGGER

SRAM POD AXS

Wireless. MMX. Right bridge.

## CHAIN

SRAM GX EAGLE

120 links. T-type.

## CASSETTE

SRAM GX

XG 1275. 10-52T. 520% range.

## CRANKSET

E\*THIRTEEN E\*SPEC PLUS

For Bosch Gen4 motor. SRAM CR Eagle Chainring 36T.  
160mm.

## COCKPIT

DEUX ENDURO BARS

Integrated bars and stem. No-bolts design. Internal fork  
tube clamp. 800mm width, 20mm rise, 40mm stem.

## BRAKES

FORMULA CURA 4

4X18mm pistons on caliper. SRAM Matchmaker. Sintered  
pads. Axial master cylinder.

## ROTORS

FORMULA CURA ROTORS

220mm front and 203mm rear. Extreme lateral stiffness,  
anti-noise design and anti-vibration technology.

## WHEELS

DT SWISS HX 1700.

29" Front. 27,5" rear. XD Mount.

## FRONT TYRE

MAXXIS ASSEGAI

29x2.50WT, 3CMaxxGrip, EXO+, TR.

## REAR TYRE

MAXXIS MINION DHR II

27.5x2.40WT, 3CMaxxTerra, DD, TR.

## SEAT POST

ONEUP DROPPER

Lever MMX. S1: 120 / S2: 150 / S3: 180mm travel..

## SADDLE

SELLE ITALIA SLR BOOST

Fibra-tek. Manganese.

Weight: 22.6kg (S2)