
Cadre

FORM™ Alloy | Full Sealed Cartridge Bearings | BSA Bottom Bracket | Internal Cable Routing | 2-Bolt ISCG05 Tabs | RIDE-4™ Adjustable Geometry | 160mm Travel. FORM™ Alloy Rear Triangle

Fourche

Fox 38 Float EVOL GRIP Performance Series 170mm | 27.5 = 37mm Offset | 29 = 44mm Offset

Amortisseur

Fox Float X Performance | Sealed Bearing Eyelet | 40x10mm F Hardware | SM = 210x55mm | MD - LG - XL = 230x60mm | Size-Specific tune in FAQ

Jeu de direction

FSA ZS56|66 Reach Adjust| 0mm Cups Installed | +/- 5mm Cups Included | Sealed Stainless 36°x45° Bearings | 30.2mm x 41mm x 7.1mm Upper | 40mm x 51.8mm x 7.5mm Lower | 1.5" Crown Race

Potence

Rocky Mountain 35 AM | 5° Rise | All Sizes = 40mm

Cintre

Rocky Mountain AM | 780mm Width | 38mm Rise | 9° Backsweep | 5° Upsweep | 35 Clamp

Poignées

ODI Elite Pro Lock On

Freins

Shimano SLX Trail 4 Piston | Metal Pads

Commande de vitesse

Shimano SLX

Dérailleur arrière

Shimano XT

Pédalier et plateau

Race Face Aeffect Cinch | 32T | 24mm Spindle | SM = 165mm | MD - XL = 170mm

Boîtier de pédalier

Shimano Threaded BBMT501-B

Cassette

Shimano Deore 10-51T 12spd

Chaîne

Shimano M6100

Roues

WTB ST i30 TCS 2.0 Tubeless | 32H / Tubeless Ready - Tape / Valves Incl

Pneus

F: Maxxis Assegai 2.5 WT 3C MaxxGrip EXO+ Tubeless Ready // R: Maxxis Minion DHR II 2.4 WT 3C

Tige de selle

X Fusion Manic 30.9mm | Shimano Remote | SM = 150mm | MD = 170mm | LG - XL = 200mm

Selle

WTB Volt Race 142

Poids

17.31 KGS

