

---

**Cadre**

SMOOTHWALL™ Carbon | Full Sealed Cartridge Bearings | BSA Bottom Bracket | Internal Cable Routing | 2-Bolt ISCG05 Tabs | RIDE-4™ Adjustable Geometry | 160mm Travel. SMOOTHWALL™ Carbon Rear Triangle

---

**Fourche**

Fox 38 Float EVOL GRIP Performance Series 170mm | 27.5 = 37mm Offset | 29 = 44mm Offset

---

**Amortisseur**

Fox Float X Performance | | 40x10mm F Hardware | SM = 210x55mm | MD - LG - XL = 230x60mm

---

**Jeu de direction**

FSA Orbit NO.85 Reach Adjust | 0mm Cups Installed | +/- 5mm Cups Included | Durable Sealed Stainless 36°x45° Bearings | 30.2mm x 41mm x 7.1mm Upper | 40mm x 51.8mm x 7.5mm Lower | 1.5"

---

**Potence**

Rocky Mountain 35 AM | 5° Rise | All Sizes = 40mm

---

**Cintre**

Rocky Mountain AM | 780mm Width | 38mm Rise | 9° Backsweep | 5° Upsweep | 35 Clamp

---

**Poignées**

ODI Elite Pro Lock On

---

**Freins**

Shimano XT Trail 4 Piston | Metal Pads

---

**Commande de vitesse**

Shimano SLX

---

**Dérailleur arrière**

Shimano XT

---

**Pédalier et plateau**

Race Face Aeffect Cinch | 32T | 24mm Spindle | SM = 165mm | MD - XL = 170mm

---

**Boîtier de pédalier**

Shimano Threaded BBMT501-B

---

**Cassette**

Shimano SLX 10-51T

---

**Chaîne**

Shimano M7100

---

**Roues**

WTB ST Light i30 TCS 2.0 Tubeless | 32H / Tubeless Ready - Tape / Valves Incl

---

**Pneus**

F: Maxxis Assegai 2.5 WT 3C R: Maxxis Minion DHR II 2.4 WT 3C // Cushcore Trail Tire Inserts

---

**Tige de selle**

X Fusion Manic 30.9mm | Shimano MT500 Remote | SM = 150mm | MD = 170mm | LG - XL = 200mm

---

**Selle**

WTB Volt Race 142

---

**Poids**

34.32|15.6 KGS