

cadre

C:62® Monocoque Advanced Twin Mold Technology, 2-Bolt ISCG05, Boost 148, UDH™

taille

29: S, M, L, XL

fourche suspendue

Fox 34 Float Rhythm, Sweep-Adjust GRIP Damper, Tapered, 15x110mm, 130mm

amortisseur

Fox Float, 190x45mm, Open/Medium/Firm Mode

frein

Shimano XT BR-M8100, Hydr. Disc Brake (203/180)

dérailleur arrière

Shimano XT RD-M8100-SGS, ShadowPlus, 12-Speed

leviers

Shimano XT SL-M8100-IR, Direct Attach

jeu de pédalier

Shimano BB-MT501, 68mm BSA

plateau

Shimano XT FC-M8100, Boost, 30T

cassette

Shimano SLX CS-M7100, 10-51T

chaîne

Shimano CN-M6100

jeu de direction

ACROS AZF-675, ICR (Integrated Cable Routing), Top Zero-Stack 1 1/2" (ZS 56mm), Bottom Zero-Stack 1 1/2" (ZS 56mm), Fiber Inserts for Angle Adjustment

Potence

CUBE Stereo Stem w/ Cable Routing

cintre

CUBE Rise Trail Bar, 760mm

poignées

ACID Disrupt, Soft Compound

roues

Newmen Beskar 30 light/base, 28/28 Spokes, 15x110mm/12x148mm, Tubeless Ready

pneus

Maxxis Forekaster, MaxxTerra/EXO, Tubeless Ready, 2.4 WT

selle

ACID Nuance Lite

tige de selle

CUBE Dropper Post, Handlebar Lever, Internal Cable Routing, 30.9mm

poids

13,4 kg