

cadre

C:62® Advanced Twin Mold Technology, Full Internal Cable Routing, Integrated Seat Post Clamp, Flat Mount Disc, Storage Box Option, AXH, 12x142mm

taille

50cm, 53cm, 56cm, 58cm, 60cm, 62cm

fourche rigide

CUBE CSL Evo Aero C:62® Technology, 1 1/8" - 1 1/4" Tapered, Flat Mount, 12x100mm

leviers de frein

Shimano 105 Di2 ST-R7170

frein

Shimano 105 BR-R7170, Hydr. Disc Brake, Flat Mount (160/160)

dérailleur arrière

Shimano 105 Di2 RD-R7150-DGS, 12-Speed

dérailleur avant

Shimano 105 Di2 FD-R7150F

jeu de pédalier

Shimano SM-BB71-41B, 86mm Pressfit

plateau

Shimano 105 FC-R7100, Hollowtech II, 50x34T

cassette

Shimano CS-R7101, 11-34T

chaîne

Shimano CN-M7100

jeu de direction

ACROS, Top Integrated 1 1/2" w/ Integrated Cable Routing, Bottom Integrated 1 1/4"

Potence

CUBE Aero Stem w/ Cable Routing

cintre

Newmen Evolution Wing Bar

Ruban de Cintre

ACID Bartape RC 3.0

roues

Newmen Evolution SL R.35, 21/21 Spokes, 12x100mm/12x142mm, Tubeless Ready

pneus

Conti Grand Prix, Kevlar, 28-622

selle

ACID Nuance Pro

tige de selle

Agree C:62 Aero, Comfort Flex

8,9 kg