

cadre

C:62® Advanced Twin Mold Technology, Full Internal Cable Routing, Integrated Seat Post Clamp, Flat Mount Disc, Storage Box Option, AXH, 12x142mm

taille

47cm, 50cm, 53cm, 56cm, 58cm, 60cm, 62cm

fourche rigide

CUBE CSL Evo Aero C:62® Technology, 1 1/8" - 1 1/4" Tapered, Flat Mount, 12x100mm

leviers de frein

Shimano Ultegra Di2 ST-R8170

frein

Shimano Ultegra BR-R8170, Hydr. Disc Brake, Flat Mount (160/160)

dérailleur arrière

Shimano Ultegra Di2 RD-R8150-DGS. 12-Speed

dérailleur avant

Shimano Ultegra Di2 FD-R8150-F

jeu de pédalier

Shimano SM-BB71-41B, 86mm Pressfit

plateau

Shimano Ultegra FC-R8100, Hollowtech II, 50x34T

cassette

Shimano Ultegra CS-R8101, 11-34T

chaîne

Shimano CN-M8100

jeu de direction

ACROS, Top Integrated 1 1/2" w/ Integrated Cable Routing, Bottom Integrated 1 1/4"

Potence

CUBE Aero Stem w/ Cable Routing

cintre

Newmen Advanced Wing Bar, Carbon

Ruban de Cintre

ACID Bartape RD

roues

Newmen Advanced A.50 Carbon, 21/21 Spokes, 12x100mm/12x142mm, Tubeless Ready

pneus

Conti Grand Prix 5000 Kevlar, 28-622

selle

ACID Nuance Pro

tige de selle

Agree C:62 Aero, Comfort Flex

poids

7,9 kg