

cadre

C:62® Twin Mold Technology, Internal Cable Routing, Integrated Seat Post Clamp, Flat Mount Disc, Storage Box Option, AXH, 12x142mm

taille

47cm, 50cm, 53cm, 56cm, 58cm, 60cm, 62cm

fourche rigide

Attain C:62®, Full Carbon, Integrated Cable Routing, Flat Mount, 12x100mm

leviers de frein

Shimano 105 Di2 ST-R7170

frein

Shimano 105 BR-R7170, Hydr. Disc Brake, Flat Mount (160/160)

dérailleur arrière

Shimano 105 Di2 RD-R7150-DGS, 12-Speed

dérailleur avant

Shimano 105 Di2 FD-R7150F

jeu de pédalier

Shimano SM-BB71-41B, 86mm Pressfit

plateau

Shimano 105 FC-R7100, Hollowtech II, 50x34T

cassette

Shimano CS-R7101, 11-34T

chaîne

Shimano CN-M7100

jeu de direction

ACROS, Top Integrated 1 1/2" w/ Integrated Cable Routing, Bottom Integrated 1 1/4"

Potence

CUBE CIS Stem w/ Cable Routing

cintre

Newmen Evolution Wing Bar

Ruban de Cintre

ACID Bartape RC 3.0

roues

Newmen Evolution SL R.35, 21/21 Spokes, 12x100mm/12x142mm, Tubeless Ready

pneus

Conti Grand Prix, Kevlar, 30-622

selle

ACID Nuance Pro

tige de selle

Newmen Advanced, Carbon, 27.2mm

poids

8,7 kg