

cadre

Litening C:68X® Air Monocoque Advanced Twin Mold Technology, Aero-Weight Optimized Tubes, Full Internal Cable Routing, Flat Mount Disc

taille

50cm, 52cm, 54cm, 56cm, 58cm, 60cm

fourche rigide

Litening C:68X® Air, Integrated Cable Routing, Flat Mount Disc

leviers de frein

Sram Force AXS™

frein

Sram Force AXS™ (160/160)

dérailleur arrière

Sram Force AXS™, 12-Speed

dérailleur avant

Sram Force AXS™

jeu de pédalier

Sram DUB Road, 86mm Pressfit

plateau

Sram Force Power Meter Carbon, 48x35T

cassette

Sram Force XG-1270, 10-33T

chaîne

Sram Force D1

jeu de direction

ACROS, Top Integrated 1 1/2" w/ Integrated Cable Routing, Bottom Integrated 1 1/4"

barre/ tige intégrée

ICR Cockpit System, Integrated Cable Routing, Aero Spacer System, Garmin Mount Interface

Ruban de Cintre

ACID Bartape RD

roues

Newmen Streem C.35/38 Carbon, 21/24 Spokes, 12x100mm/12x142mm, Tubeless Ready

pneus

Conti Grand Prix 5000 S TR, 28-622

selle

ACID Nuance SLT Road Carbon

tige de selle

Litening C:68X® Aero, Comfort Flex

extras

tubolito  Inner Tubes

poids

7,2 kg