

cadre

C:68X® Monocoque Advanced Twin Mold Technology, FSP 4-Link, Boost 148, UDH™

taille

29: S, M, L, XL

fourche suspendue

Fox 34 SC Float Factory GRIP SL, 2-Position Remote, Tapered, 15x110mm, 110mm, Kashima Coated

amortisseur

Fox Float SL Factory Remote, 190x40mm, 2-Position Remote, Kashima Coated

entretoises d'amortisseur

Front: 26x8mm, Rear: 30x8mm

frein

Magura MT8 SL, Hydr. Disc Brake (180/160)

dérailleur arrière

Sram X0 Eagle AXS™ Transmission, 12-Speed, Electronic Shifting System

leviers

Sram AXS™ Pod Controller

jeu de pédalier

Sram DUB MTB Wide, 92mm Pressfit

plateau

Sram X0 Eagle™ Transmission, 32T

cassette

Sram XS-1275, 10-52T

chaîne

Sram GX Eagle™ Transmission

jeu de direction

ACROS Integrated, Top 1 1/8", Bottom 1 1/2", Fiber Inserts for Angle Adjustment

Potence

Newmen Evolution SL 318.2, 31.8mm

cintre

Newmen Advanced 318.0, Carbon, 740mm

poignées

ACID Disrupt, Soft Compound

roues

Newmen Phase 30 light/light Carbon, 28/28 Spokes, 15x110mm/12x148mm, Tubeless Ready

pneu avant

Schwalbe Racing Ray, Super Race, Addix Speed, Kevlar, 2.35

pneu arrière

Schwalbe Racing Ralph, Super Race, Addix Speed, Kevlar, 2.35

selle

ACID Nuance SLT X Carbon

tige de selle

Fox Transfer Factory 30.9mm, Kashima Coated

extras

Schwalbe Aerothan™ Inner Tubes

poids

10,7 kg