

cadre

C:62® Monocoque Advanced Twin Mold Technology, Aluminium 6061 T6 Rear Triangle, Efficient Trail Control, FSP 4-Link, Agile Trail Geometry, Boost 148, UDH™, Full Integrated Battery, Advanced Internal Cable Routing

taille

Size Split: 27.5: S // 29: M L XL

fourche suspendue

Fox 36 Float Factory GRIPX, 2-Position w/High/Low Speed Compression Adjust, Tapered, 15x110mm, E-Bike Optimized, 150mm, Kashima Coated

amortisseur

Fox Float X Factory, 230x60mm (27.5: 210x55mm), Adjustable LSC w/ 2-Pos. Lever, Kashima Coated

entretoises d'amortisseur

Front: 30x8mm, Rear: DU-Bushing 12,7mm

moteur

Bosch Drive Unit Performance Line CX 85Nm (BDU38), Smart System



[Voir les détails](#)

Télécommande

Bosch System Control, incl. Mini Remote



[Voir les détails](#)

batterie

Bosch PowerTube 800



[Voir les détails](#)

écran

Bosch Purion 400



[Voir les détails](#)

chargeur
Bosch 4A



[Voir les détails](#)

frein

Shimano XT BR-M8120, Hydr. Disc Brake (203/203)

dérailleur arrière

Sram X0 Eagle AXS™ Transmission, 12-Speed, Electronic Shifting System

leviers

Sram AXS™ Pod Controller

plateau

ACID MTB Hybrid Pro, 27.5: 36T // 29: 34T

cassette

Sram XS-1275, 10-52T

chaîne

Sram GX Eagle™ Transmission

guide de chaîne

Reverse Flip-Guide E-Chain Guide, Direct Mount, I-Plate

jeu de direction

ACROS AZF-675, ICR (Integrated Cable Routing), Top Zero-Stack 1 1/2" (ZS 56mm), Bottom Zero-Stack 1 1/2" (ZS 56mm), Fiber Inserts for Angle Adjustment, X-Connect Interface

Potence

CUBE Performance Stem E-MTB 35, FPI-Link

cintre

Race Face ERA 35

poignées

ACID Disrupt

roues

Newmen Beskar 30 base/strong, 28/32 Spokes, 15x110mm/12x148mm, Tubeless Ready

pneu avant

Schwalbe Magic Mary, Addix Soft, Super Trail, Kevlar, 2.4

pneu arrière

Schwalbe Big Betty, Addix Soft, Super Gravity, Kevlar, 2.4

selle

ACID Venec EMTB Trail 140

tige de selle

Fox Transfer Factory 31.6mm, Kashima Coated