

cadre

C:62® Monocoque Advanced Twin Mold Technology, Aluminium 6061 T6 Rear Triangle, Efficient Trail Control, FSP 4-Link, Agile Trail Geometry, Boost 148, UDH™, Full Integrated Battery, Advanced Internal Cable Routing

taille

S, M, L, XL

fourche suspendue

Fox 38 Float GRIP, 3-Position w/Micro Adjust, Tapered, 15x110mm, E-Bike Optimized, 170mm

amortisseur

Fox Float X2 Performance, 230x65mm, Low Speed Rebound & Compression w/ 2-Position Lever

entretoises d'amortisseur

Front: 30x8mm, Rear: DU-Bushing 12,7mm

Moteur Bosch Drive Unit Performance Line CX 85Nm (BDU38), Smart System



Télécommande Bosch System Control, incl. Mini Remote



batterie Bosch PowerTube 800



écran Bosch Purion 400



chargeur Bosch 4A



freins

Magura MT7, Hydr. Disc Brake (203/203)

dérailleur arrière

Sram GX Eagle AXS™ Transmission, 12-Speed, Electronic Shifting System

Commandes

Sram AXS™ Pod Controller

cassette

Sram XS-1275, 10-52T

chaîne

Sram GX Eagle™ Transmission

Guide-chaîne

Reverse Flip-Guide E-Chain Guide, Direct Mount, I-Plate

jeu de direction

ACROS AZF-675, ICR (Integrated Cable Routing), Top Zero-Stack 1 1/2" (ZS 56mm), Bottom Zero-Stack 1 1/2" (ZS 56mm), Fiber Inserts for Angle Adjustment, X-Connect Interface

Potence

CUBE Performance Stem E-MTB 35, FPI-Link

cintre

CUBE Rise Trail Bar 35

poignées

ACID Disrupt, Soft Compound

roues

Newmen Beskar 30 base/strong, 28/32 Spokes, 15x110mm/12x148mm, Tubeless Ready

pneu avant

Schwalbe Magic Mary, Addix Soft, Super Trail, Kevlar, 2.4

pneu arrière

Schwalbe Tacky Chan, Addix Soft, Super Gravity, Kevlar, 2.4

selle

ACID Venec EMTB Trail 140

tige de selle

CUBE Dropper Post, Handlebar Lever, Internal Cable Routing, 31.6mm

couleur

dustyolive'n'gold

poids

24,3 kg