

cadre

C:62® Monocoque Advanced Twin Mold Technology, Aluminium 6061 T6 Rear Triangle, Efficient Trail Control, FSP 4-Link, Agile Trail Geometry, Boost 148, UDH™, Full Integrated Battery, Advanced Internal Cable Routing

taille

S, M, L, XL

fourche suspendue

Fox 38 Float Factory GRIPX2, Tapered, 15x110mm, E-Bike Optimized, 170mm, Kashima Coated

amortisseur

Fox Float X2 Factory, 230x65mm, High/Low Speed Rebound & Compression w/ 2-Position Lever, Kashima Coated

entretoises d'amortisseur

Front: 30x8mm, Rear: DU-Bushing 12,7mm

Moteur Bosch Drive Unit Performance Line CX 85Nm (BDU38), Smart System



Télécommande Bosch System Control, incl. Mini Remote



batterie Bosch PowerTube 800



écran Bosch Purion 400



chargeur Bosch 4A



freins

Shimano XT BR-M8120, Hydr. Disc Brake (203/203)

dérailleur arrière

Sram X0 Eagle AXS™ Transmission, 12-Speed, Electronic Shifting System

Commandes

Sram AXS™ Pod Controller

Pédalier

ACID MTB Hybrid Pro, 36T

cassette

Sram XS-1275, 10-52T

chaîne

Sram GX Eagle™ Transmission

Guide-chaîne

Reverse Flip-Guide E-Chain Guide, Direct Mount, I-Plate

jeu de direction

ACROS AZF-675, ICR (Integrated Cable Routing), Top Zero-Stack 1 1/2" (ZS 56mm), Bottom Zero-Stack 1 1/2" (ZS 56mm), Fiber Inserts for Angle Adjustment, X-Connect Interface

Potence

CUBE Performance Stem E-MTB 35, FPI-Link

cintre

Race Face ERA 35

poignées

ACID Disrupt, Soft Compound

roues

Newmen Beskar 30 base/strong, 28/32 Spokes, 15x110mm/12x148mm, Tubeless Ready

pneu avant

Schwalbe Magic Mary, Addix Soft, Super Trail, Kevlar, 2.4

pneu arrière

Schwalbe Tacky Chan, Addix Soft, Super Gravity, Kevlar, 2.4

selle

ACID Venec EMTB Trail 140

tige de selle

Fox Transfer Factory 31.6mm, Kashima Coated

couleur

actionteam

poids

24,1 kg